



Motorized polarization rotator MRO

Main features

- Compact design
- High resolution 175543 μ steps in 360 deg rotation
- High accuracy - ± 10 μ steps accuracy ($\pm 0,02$ deg)
- Clear aperture - 18 mm
- Fast adjustment - less than 0,2 sec (0 to 45 deg)

Rotator (MRO) is a compact motorized device for laser polarization control. The MRO is produced in the UV, visible and NIR spectral ranges, from 250 nm to 2000 nm. The device has external controller. All optical components of the MRO are made for high LIDT and provide stable and reliable performance even using them with high power lasers in industrial applications.

Standard specifications

SPECIFICATIONS	
Clear aperture	ϕ 18 mm
Standard wavelengths	257 nm; 343 nm; 355 nm; 400 nm; 515 nm; 532 nm; 800 nm; 1030 nm; 1064 nm
LIDT coating	>10 [J/cm ²] (10 ns @ 1064 nm)
Close to open time (0 to 45 deg)	< 0,2 sec
Resolution	175,543 μ steps in full rotation 21,943 μ steps in 45deg rotation (0,002 deg, 7,2 arcsec, 0,035 mrad)
Accuracy	± 10 μ steps ($\pm 0,02$ deg)
Motor	2 phase stepper motor, 200 steps with 256 μ stepping
Mechanical dimensions	37,5 x 36 x 58 mm
Controller mechanical dimensions	125 x 53 x 31 mm
Software	LPA software

Standard products

CLEAR APERTURE	CONTROL INTERFACE	WAVEPLATE	RETARDATION	LIDT	SKU	PRIC
18 mm	USB or RS232	1064 nm	L/2	10 J/cm ² (10 ns@1064 nm)	19706	
		1030 nm	L/2	10 J/cm ² (10 ns@1030 nm)	19572	
		532 nm	L/2	5 J/cm ² (10 ns@532 nm)	19705	
		515 nm	L/2	5 J/cm ² (10 ns@515 nm)	19700	
		355 nm	L/2	3 J/cm ² (10 ns@355 nm)	19702	
		343 nm	L/2	3 J/cm ² (10 ns@343 nm)	19701	
		266 nm	L/2	2 J/cm ² (10 ns@266 nm)	19703	
		257nm	L/2	2 J/cm ² (10 ns@257 nm)	19704	
		1064 nm	L/4	10 J/cm ² (10 ns@1064 nm)	19708	
		1030 nm	L/4	10 J/cm ² (10 ns@1030 nm)	19479	
		532 nm	L/4	5 J/cm ² (10 ns@532 nm)	19709	
		515 nm	L/4	5 J/cm ² (10 ns@515 nm)	19478	
		355 nm	L/4	3 J/cm ² (10 ns@355 nm)	13527	
		343 nm	L/4	3 J/cm ² (10 ns@343 nm)	19477	
		266 nm	L/4	2 J/cm ² (10 ns@266 nm)	19711	
		257nm	L/4	2 J/cm ² (10 ns@257 nm)	19710	
		without optics	None	None	19707	


www.phototechnica.co.jp
 フォトテクニカ株式会社
 〒336-0017 埼玉県さいたま市南区南浦和 1-2-17
 TEL:048-871-0067 FAX:048-871-0068
 e-mail:voc@phototechnica.co.jp