


3719 Warren Avenue · Bellwood, IL 60104 · 708 547-6644 · Fax 708 547-0687 · iac@intraaction.com

## MODEL FCM SERIES FIBER PIGTAILED ACOUSTO-OPTIC MODULATOR/ATTENUATOR

- NEAR IR WAVELENGTH RANGE
- INTENSITY MODULATION
- OPTICAL FREQUENCY SHIFTING
- CHOICE OF FREQUENCY SHIFT
- LOW RF DRIVE POWER
- HIGH RELIABILITY



### SPECIFICATIONS

Acousto-optic Material	AMTIR-1 Chalcogenide Glass
Optical Fiber <sup>1</sup>	Singlemode
Fiber Connector <sup>1</sup>	FC-PC
Optical Back Reflection <sup>2</sup>	-40 dB
Optical Polarization	any
Input Impedance / VSWR	50 Ohms / 1.2:1
Size	See outline drawing

MODEL (Modulator) <sup>3</sup>	<u>FCM-40.8E5C</u>	<u>FCM-40.8E6C</u>	<u>FCM-401E5C</u>	<u>FCM-401E6C</u>
Optical Wavelength	1.55 μm	1.3 μm	1.55 : m	1.3 : m
RF Frequency <sup>4</sup>	40 MHz	40 MHz	40 MHz	40 MHz
Optical Frequency Shift	+ 40 MHz	+ 40 MHz	+ 40 MHz	+ 40 MHz
RF Drive Power <sup>5</sup>	600 mwatts	500 mwatts	500 mwatts	400 mwatts
Insertion Loss (RF on)	< 3 dB	< 3 dB	< 2.4 dB	< 2.4 dB
Extinction Ratio (RF on/RF off) <sup>5</sup>	> 55 dB	> 55 dB	> 55 dB	> 55 dB
Modulation Bandwidth (-3 dB)	7.5 MHz	7.5 MHz	4 MHz	4 MHz
Optical Rise Time	60 nsec	60 nsec	120 nsec	120 nsec

MODEL (Attenuator) <sup>3</sup>	<u>FCM-40.8E5CA</u>	<u>FCM-40.8E6CA</u>	<u>FCM-401E5CA</u>	<u>FCM-401E6CA</u>
Optical Wavelength	1.55 μm	1.3 μm	1.55 : m	1.3 : m
RF Frequency <sup>4</sup>	40 MHz	40 MHz	40 MHz	40 MHz
RF Drive Power <sup>5</sup>	600 mwatts	500 mwatts	500 mwatts	400 mwatts
Insertion Loss (RF off)	< 1 dB	<1 dB	< 1 dB	< 1 dB
Extinction Ratio (RF off/RF on)	7 dB	7dB	7dB	7 dB
Modulation Bandwidth (-3 dB)	7.5 MHz	7.5 MHz	4 MHz	4 MHz
Optical Rise Time	60 nsec	60 nsec	120 nsec	120 nsec

<sup>1</sup> Other optical fiber such as polarization maintaining, and other connectors such as FC-APC are also available.

<sup>2</sup> Optical back reflection varies with fiber type and connectors.

<sup>3</sup> Modulator...first order diffracted beam is transmitted to output fiber, Attenuator...zero order beam is transmitted to output fiber.

<sup>4</sup> Operation at other RF frequencies is available. See Frequency Shifter/FCM Series product sheet.

<sup>5</sup> High extinction digital drivers are available. Laboratory and OEM drivers are available.